

Referans Nr.	Sıkma Yüksekliği Clamping Height				Sıkma Torku Clamping Stroke	İnme Torku Advance Stroke	L2	L3	L1	L4	W	L	H5	B
	Finiş Yüzey Temas Finished Surface Contact		Kaba Yüzey Temas Rough Surface Contact											
	Min.	Max.	Min.	Max.										
1482-0150R	31.3 (30.8-31.8)	33.3 (32.8-33.8)	32.2 (31.7-32.7)	34.2 (33.7-34.7)	1	1.5	30	8	35	15.3	45	23	8	5.3
1482-0150L														
1482-0200R	32.5 (31.9-33.1)	39 (38.4-39.6)	33.5 (32.9-34.1)	40 (39.4-40.6)	1.2	1.8	37	8	45	20.7	65	30	12	8.4
1482-0200L														
1482-0300R	36.5 (35.7-37.2)	46 (45.2-46.7)	39 (38.2-39.7)	48.5 (47.7-39.2)	1.5	2.3	45	8	55	25.4	85	40	15	10.5
1482-0300L														

Referans Nr.	Dp	H	D	W1	W2	H3	H2	M	H4	R	A	H1	Izin Verilen Çalışma Yüğü Allowable Operating Load (N)	Sıkma Kuvveti Clamping Force Kgf
1482-0150R	34	131	23	10	5.3	14	40	M5	28.5	63	19	68	150	150
1482-0150L														
1482-0200R	48	167	30	16	8.4	18	50	M8	45.5	80	24	87	200	210
1482-0200L														
1482-0300R	64	207	40	20	10.4	22	60	M10	57	100	30	107	300	280
1482-0300L														

Ürün Nr. 1482 Tek Dokunuş Dönmeli Üstten Bağlama

Gövde

- Malzeme: Ck45 DIN
- Sertlik: 28-32 HRC
- Siyah Kaplama

Sıkma Pabucu

- Malzeme: 42 CrMo 4 DIN
- Sertlik: 38-42 HRC
- Siyah Kaplama

Product Nr. 1482 Swing Clamps With Cam Handle

Body

- Material: Ck45 DIN
- Hardness: 28-32 HRC
- Black coated

Clamping Arm

- Material: 42 CrMo 4 DIN
- Hardness: 38-42 HRC
- Black coated

