




Referans Nr.	a	s1	m	sw	L	h	k	n	Sıkma Kuvveti Clamping Force	
									kgf	(g)
2150-08	8	1.3	5	4	23	9.5	5	7.7	310	25
2150-10	10	1.4	5	4	23	14	5	9.7	310	35
2150-12	12	1	7	5	28	15	6	11.7	340	60
2150-14	14	1.5	7	8	30	22	8	13.7	800	95
2150-16	16	2	10	8	30	22	9	15.7	1500	130
2150-18	18	2	10	8	35	28	10	17.7	1500	190
2150-20	20	2.5	13	10	40	32	12	19.7	2000	290
2150-22	22	2.5	13	12	45	38	14	21.7	2000	390

Ürün Nr. 2150 Kanal İçi Yandan Bağlama

- Ürünün "T" gövdesi tamamiyle tezgah kanalına girer. Sadece ürünün eksantrik başlığı tabla yüzeyinde kaldığı için ince parçalarda sıkma kolaylığı sağlar.
- DIN 650 "T" kanala uyumludur
- Malzeme Ck45 DIN
- Sertlik 38 HRC
- Siyah kaplama

Product Nr. 2150 In-slot Side Clamp

- "T" slot of the product enters in the slot of the bench completely. Since only the eccentric headpiece remains on the surface of the table, this provides easy clampings of the thin pieces.
- It is in compliance with DIN 650 "T" Slot
- Material: Ck45 DIN
- Hardness: 38 HRC
- Black coating



Yandan Bağlama Pençe Pabuç

Jaw Clamp

Referans Nr.	a	c	n		x	L	b	m1	sw	Sıkma Kuvveti Clamping Force		(g)
			min	max						f1 kgf	f2 kgf	
2170-12	12	2	2	6	4	46	18	7	5	500	60	120
2170-14	14	2.5	2.5	7.5	5	51	22	8	6	550	70	200
2170-16	16	3	2.5	8.5	6	61	25	9	6	800	90	290
2170-18	18	3	2	8	6	67	28	10	8	900	100	420
2170-20	20	4	2.5	11	8.5	78	32	12	10	1200	140	640
2170-22	22	4.5	2.5	12	9.5	87	35	14	10	1600	190	830

Ürün Nr. 2170 Yandan Bağlama Pençe Pabuç

- İş parçasını dayama ve pleyt yönüne sıkar
- "T" kanal içinde çalışması yükseklik avantajı sağlar
- DIN 650 "T" kanala uyumludur
- Malzeme Ck45 DIN
- Sertlik 38 HRC
- Siyah kaplama

Product Nr. 2170 Jaw Clamp

- This product clamps the workpiece in the direction of resting and plate
- It's working in "T" slot provides height advantage
- It is in compliance with DIN 650 "T" Slot
- Material: Ck45 DIN
- Hardness: 38 HRC
- Black coating

