



MORS KONİK SAPLI MAKİNA RAYBASI DIN 208B, HELİS, HSS,H7				HSS
D H7 (mm)	L (mm)	l (mm)	MK	IAT208B FİYAT KODU
6	138	26	1	04814
7	150	31	1	04815
8	156	33	1	04816
9	162	36	1	04817
10	168	38	1	04818
11	175	41	1	04819
12	182	44	1	04820
13	182	44	1	04821
14	189	47	1	04822
15	204	50	2	04823
16	210	52	2	04824
17	214	54	2	04825
18	219	56	2	04826
19	223	58	2	04827
20	228	60	2	04828
21	232	62	2	04829
22	237	64	2	04830
23	241	66	2	04831
24	268	68	3	04832
25	268	68	3	04833
26	273	70	3	04834
27	277	71	3	04835
28	277	71	3	04836
29	281	73	3	04837
30	281	73	3	04838
31	285	75	3	04839
32	317	77	4	04840
33	317	77	4	04841
34	321	78	4	04842
35	321	78	4	04843
36	325	79	4	04844
38	329	81	4	04845
39	329	81	4	04846
40	329	81	4	04847
41	333	82	4	04848
42	333	82	4	04849
44	336	83	4	04850
45	336	83	4	04851
46	340	84	4	04852
47	340	84	4	04853
48	344	86	4	04854
50	344	86	4	04855

**KULLANIM ALANI**

Kısa kesme ağızlı ve mors konik saplı rayba. Eşit bölümlü olmayan kesme ağızlarıyla, silindirik ve düzgün bir raybalama imkanı verir. Bütün çelik türlerinde, NE- metallerde, sert ve yumuşak plastiklerde, kördelikler için H7 delik toleranslarında raybalama işlemi için kullanılır.