



HSS

MAKİNA KILAVUZU DIN 5156C 35 DERECE HELİS								HSS
								C.5156C
d ₁	P	l ₁	l ₂	d ₂	a	z	MATKAP ÇAPı Ø mm	FİYAT KODU
G 1/16"	28	90	18	6	4,9	3	6,8	07740
G 1/8"	28	90	20	7	5,5	3	8,8	07741
G 1/4"	19	100	21	11	9	3	11,8	07742
G 3/8"	19	100	21	12	9	3	15,25	07743
G 1/2"	14	125	24	16	12	3	19	07744
G 5/8"	14	125	24	18	14,5	4	21	07745
G 3/4"	14	140	26	20	16	4	24,5	07746
G 7/8"	14	150	28	22	18	4	28,25	07747
G 1"	11	160	30	25	20	4	30,75	07748
G 1 1/8"	11	170	30	28	22	4	35,5	07749
G 1 1/4"	11	170	30	32	24	4	39,5	07750
G 1 3/8"	11	180	32	36	29	6	41,8	07751
G 1 1/2"	11	190	32	36	29	6	45,25	07752
G 1 3/4"	11	190	32	40	32	6	51,3	07753
G 2"	11	220	40	45	35	6	57,2	07754
<p>HSS → Yüksek hız çeligi</p>							<p>KULLANIM ALANI</p>	<p>ANA KULLANIM</p> <ul style="list-style-type: none"> Kolay işlenir çelikler (max. 800N/mm²) Yalın Dökme demir (max. 800N/mm²) Yapısal çelikeler (max. 500N/mm²)